



Bury-27 Series
Inground / Inwater Light




- Code Product: Bury 27-Series
- Dimension: Ø213mm x H77mm(IP68: H: 65); Cutout: Ø350x190mm
- Input Voltage: IP68-12VAC/24VDC/ 110-240VAC (43-60Hz)
- Power consumption: Max 65W (27 - 65W)
- Luminous Flux: 4680Lm at 54W 3000K, 24VDC, CRI>80
- Brand of LEDs: LED CREE
- Color: 3000K - CRI: > 80 (Single Color; RGB; RGBW)
- Beam Angle: 15° (orther angle please contact us)
- Function Dimmer: Option
- Material: Body: IP67-Body: Aluminium Anode ; Face: Inox316
- IP68- Full Stainless 316
- Finishing (Color housing): Stainless
- IP Class: 67 for Inground; 68 for Inwater
- Class: III for IP68; I for IP67

- LED lifetime: 50.000hrs
- Lens: Clear
Cellular
Sand | Material PMMA
with UV protection
- Standards:
 - +EMC protection
 - +IEC 62031 LED modules for
general lighting Safety specifications
 - +IEC 60598 Luminaires – Parts 1+2:
General requirements
particular requirementsand tests





IP67




4680Lm at 54W 3000K, 24VDC, CRI>80

Product Description	
Control Gear	Fairchild Technology
LED Module	High-power LEDs on metal-core PCB. Collimating lens made of optical polymer/pmma
Anti-Glare	Option
Electrical Protection	EMC, inrush current
Electrical Class	3







1



2



3



4

