




Sana-4 Series

Projector For Facade Light



- Code Product: Sana-4 Series
- Dimension: 56mm x 56mm x 91mm
- Input Voltage: 24VDC / 110-240VAC (43-60Hz)
- Power consumption: Series 4 (4-8W)
- Luminous Flux: 320 Lm at 3000K, 60°, 4W
- Brand of LEDs: LED CREE
- Color: 3000K, CRI > 80, 3-Step Macadam Ellipse
- Angle: 6° (6, 10°, 24, 36°, 45°, 60°)
- Function Dimmer: None
- Material: Aluminium
- Finishing (Color housing): Anode Black
- IP Class: 66
- Electrical Class: I


- LED lifetime: 50.000hrs
- Lens: Clear
Cellular
Sand
- Standards:
 - +EMC protection
 - +IEC 62031 LED modules for general lighting Safety specifications
 - +IEC 60598 Luminaires – Parts 1+2: General requirements particular requirements and tests

Material PMMA
with UV protection










Pending

IP66



Product Description	
Control Gear	Fairchild Technology
LED Module	High-power LEDs on metal-core PCB. Collimating lens made of optical polymer/pmma
Anti-Glare	Option
Electrical Protection	EMC, inrush current
Electrical Class	3



Spike accessories of Sana

